

Project	Type
Catalog #	

DESCRIPTION

The L-Trim SOL Recessed LED Downlight is one of the most aesthetically pleasing solid state downlights in the market and is suitable for both, remodel and new construction applications. The L-Trim SOL is suitable for all commercial, retail, institutional, and residential applications.



FEATURES AND SPECIFICATIONS

- Compatible with most 6" recessed housings
- Easy installation with adjustable torsion springs
- Integrated trim
- Durable construction
- Edison Base and GU24 socket adaptors included
- 5-year warranty
- Dimmable via Mark 7 (0-10V) dimming interface

CERTIFICATION

- UL Listed - New Construction (E344008)
- UL Listed - Retrofit (E352453)
- Energy Star Approved



PRODUCT INFO	3500K	4000K	5000K
Input Voltage (VAC)	120-277	120-277	120-277
System Level Power (W)	15.5	15.5	15.5
Delivered Lumens (Lm)	1500	1510	1570
System Efficacy (Lm/W)	97	97	101
Color Rendering Index	80	80	80
L70 Calculated Life (Hrs)*	> 200,000	> 200,000	> 200,000

* US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors

ORDERING INFORMATION

Example: LTR2-1-UNV-35-15-6R-V-WH

Series	Variant	Voltage	CCT	Power	Size	Mount	Color
LTR2	1	UNV 120-277	35 3500K 40 4000K 50 5000K	15 15W	6R 6" Round	V V-Spring (Retrofit) C Clamp (New Construction)	WH White