

QubePAK 1M

Wall Pack Luminaire
1-Qube, 120-277V Input



Description

For exterior wall lighting applications in new construction or retrofit opportunities, USLED has the QubePAK 1M. The QubePAK 1M simulates the all-too-familiar design of the popular 250W metal halide wall packs, but instead houses a LED light engine that maintains expected light output at a 70% reduction in energy. The QubePAK 1M is ideal for institutional and commercial exterior general lighting applications.

Features

- Low voltage Class 2 design
- Uses at least 70% less power than equivalent metal halide
- 5-year warranty

Certifications

- UL Listed USA and Canada (# E338791)
- LM-79 available



Project	Type
Catalog Number	

QubePAK1M



Energy Data

Input Voltage (VAC)	120-277
System Level Power (W)**	42.5
Delivered Lumens (Lm)	4,125
System Efficacy (Lm/W)**	97
Color Temperature (K)	5000K
Color Rendering Index (CRI)	80 min
L70 Calculated Life (Hrs)*	>200,000
L70 Calculated Life (Hrs)*	107,000
Operating Temp (°C)	-40 to 35

* US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.

** Measured at 277VAC

Specifications

Dimensions (in)	14.3" x 9" x 7.7"
Units / Carton	1
Net Weight	11 lbs
Environmental Rating	Wet

Fixture Ordering Information

Example: QL3-1-UNVL-4-5-50-0

Series	Fixture Style	Variant	Input Voltage	Qube LED Array	LED Type	# of Qubes	Light Pattern	Fixture Color
DS	402U	2	UNV 120-277	QB3	NC	1	L Lambertian	BZ Bronze ***WT White ***BK Black ***SV Silver



UPDATED 7/27/2016

Specifications and dimensions subject to change without notice.